



165 KVA STANDBY OPEN SET JOHN DEERE



TECHNICAL INFORMATION

Voltage (V):	400/230
Frequency (Hz):	50
PRP Power (kVA)	150
Standby Power (kVA)	165
PRP Power (kW)	120
Standby Power (kW)	132

Weight and Dimensions (mm)

Length (L)	2495
Width (W)	980
Height (H)	1885
Weight (kg)	1480
Fuel tank capacity (l)	248

Consumption

	PRP Power	
	L/h	Range (hours)
25%	9.3	26.7
50%	18	13.8
75%	26.6	9.3
100%	34.4	7.2

	Standby Power	
	L/h	Range (hours)
25%	10.1	24.6
50%	19.8	12.5
75%	28.9	8.6
100%	37.8	6.6

ENGINE

Brand	JOHN DEERE
Model	6068HF158
No. of cylinders	6
Engine Capacity (c.c)	6800
Bore (mm)	106
Stroke (mm)	127
Compression ratio	17:1
Water cooled	YES
Speed (R.P.M)	1500
Mechanical Net Power (kWm)	148
Fuel tank capacity (l)	248

Cooling System

Flow of air from fan (m3/min)	162
-------------------------------	-----

Lubrication System

Oil sump capacity (l)	19
Maximum oil consumption (% fuel consumption)	0.2

Air intake system

Aspirated air flow (m3/min)	11.2
-----------------------------	------

Electrical System

Number of batteries	1
Battery	12V 44Ah-730A

Exhaust System

Input diameter (")	4
Output diameter (")	4
Body diameter (mm)	198
Exhaust length (mm)	740
T ^a gas emission (°C)	575
Gas flow (m3/min)	25.4

ALTERNATOR

Model	LSA 44.2 M95
Electronic Regulation	YES
AVR	R 250
Power (kVA)	165

ELECTRIC PANEL

Protection Devices	YES
Control Card	DEEP SEA 7320