



415 KVA STANDBY OPEN SET VOLVO



TECHNICAL INFORMATION

Voltage (V):	400/230
Frequency (Hz):	50
PRP Power (kVA)	377.8
Standby Power (kVA)	413.9
PRP Power (kW)	302.3
Standby Power (kW)	331.1

Weight and Dimensions (mm)

Length (L)	3430
Width (W)	1150
Height (H)	2210
Weight (kg)	3530
Fuel tank capacity (l)	527

Consumption

	PRP Power	
	L/h	Range (hours)
25%	21.9	24.1
50%	39.4	13.4
75%	57	9.2
100%	75.7	7

	Standby Power	
	L/h	Range (hours)
25%	23.5	22.4
50%	42.6	12.4
75%	62	8.5
100%	83.5	6.3

ENGINE

Brand	VOLVO
Model	TAD 1343 GE
Electronic Management	YES
No. of cylinders	6
Engine Capacity (c.c)	12780
Bore (mm)	131
Stroke (mm)	158
Compression ratio	18.1:1
Water cooled	YES
Speed (R.P.M)	1500
Mechanical Net Power (kWm)	356
Fuel tank capacity (l)	527

Cooling System

Flow of air from fan (m3/min)	408
Water Jacket Heater	YES

Lubrication System

Oil sump capacity (l)	36
Maximum oil consumption (% fuel consumption)	0.4

Air intake system

Aspirated air flow (m3/min)	27
-----------------------------	----

Electrical System

Number of batteries	2
Battery	12V 44Ah-730A

Exhaust System

Input diameter (")	5
Output diameter (")	5
Body diameter (mm)	249
Exhaust length (mm)	840
T ^a gas emission (°C)	420
Gas flow (m3/min)	60

ALTERNATOR

Model	LSA 47.2 S4
Electronic Regulation	YES
AVR	R 450
Power (kVA)	450

ELECTRIC PANEL

Protection Devices	YES
Control Card	DEEP SEA 7320